

PROJECTILE 419 F

Uniform and economical
lubrication thanks to patented
nozzle system



The PROJECTILE 419F ensures uniform lubrication for all knitting components, incl. needles, cams and lifters. The patented nozzle construction separates the air-oil mixture into air and droplets of oil. This means that the oil only goes to the components requiring lubrication, so avoiding the formation of oil mist in the knitting workshop.

This unit impresses with its outstanding economy and range of integrated functionalities. The many features of the unit include a safety pressure valve, a float switch for switching off the machine when the minimum oil level is reached, an integrated pressure gauge to ensure optimum pressure in the PROJECTILE 419F, an easily accessible oil drain screw and a pressure-relief valve. An optional separate maintenance unit can also be connected up.

ADVANTAGES

- The patented atomizing and nozzle system enables a major reduction in compressed air consumption. This enables considerable savings in power and operating costs.
- Uniform delivery of oil for up to 28 lubrication points and to 2 low-flow lubrication points.
- Tank volume approx. 3.2 litres
- Sturdy, user-friendly design
- Simple handling (installation, electrical connection, filling, oil drainage)
- Integrated unit monitoring (float switch, safety pressure valve, pressure-relief valve)
- Integrated pressure regulator
- Adaptation feature for separate maintenance unit



▶ Projectile 419F

Components PROJECTILE 419 F

PRESSURE REGULATOR

Built-in device to adjust pressure levels inside the tank.

PRESSURE-RELIEF VALVE

Monitors the pressure inside the tank to prevent excess pressure.

ELECTRICAL CONNECTION CABLE

Customer-specific, easy to connect.

FLUSHER UNIT

The flusher unit flushes and cleans knitting components. This is designed for both manual and electrical control.



ADAPTABLE MAINTENANCE UNIT

Can be adapted to lubricator if necessary. Option: Pressure controller to monitor the pressure inside the tank to prevent any drop in pressure.

OIL DRAIN SCREW

Simple to access from the front of the unit.

FLOAT SWITCH

Monitors the oil filling level.

TANK FILLING PORT

Very large filling opening makes it easy to top up oil.

ADVANCED KNITTING TECHNOLOGY

MEMMINGER-IRO GMBH
 Jakob-Mutz-Straße 7 | 72280 Dornstetten-Germany
 Tel. +49 7443 281-0 | info@memminger-iro.de
 www.memminger-iro.de

